

Printing date 07.12.2009

Revision: 07.12.2009

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- Trade name: GEBOSIL S-BITUM
- Article number: SILBN01
- · Application of the substance / the preparation Bitumen sealing
- Manufacturer/Supplier: G&B Fissaggi Srl Corso Savona 22 10029 Villastellone (TO) Netherlands Tel: +39 011 96 19 433 Fax: +31 011 96 19 639 E-mail: info@gebfissaggi.com Internet: www.gebfissaggi.com
- Further information obtainable from: Product safety department. info@gebfissaggi.com
- Information in case of emergency: info@gebfissaggi.com Tel.: +39 011 96 19 433

2 Hazards identification

- · Hazard description: Not applicable.
- · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. R 10 Flammable.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- · Chemical characterization
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 2)

R 10-66-67 10-30%



Printing date 07.12.2009

Revision: 07.12.2009

Trade name: GEBOSIL S-BITUM

(Contd. of page 1)

5 Fire-fighting measures

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water. • Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate (10-30%)

- WEL Short-term value: 966 mg/m³, 200 ppm
 - Long-term value: 724 mg/m³, 150 ppm

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.



Printing date 07.12.2009

Revision: 07.12.2009

Trade name: GEBOSIL S-BITUM

(Contd. of page 2)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties				
· General Information				
Form: Colour: Odour:	Pasty Black Characteristic			
 Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 124°C 				
· Flash point:	21 - 55°C			
· Ignition temperature:	370°C			
· Self-igniting:	Product is not selfigniting.			
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.			
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %			
· Vapour pressure at 20°C:	10.7 hPa			
· Density at 20°C:	1.3 g/cm ³			
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.			
· pH-value:	Undetermined.			
 Solvent content: VOC (EC) VOC (EC) 	11.00 % 143.0 g/l			

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Dangerous reactions No dangerous reactions known.
- \cdot Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.

(Contd. on page 4)



Printing date 07.12.2009

Revision: 07.12.2009

Trade name: GEBOSIL S-BITUM

 $(Contd. \ of \ page \ 3)$

• on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)				
٠				
· ADR/RID class:	3 Flammable liquids.			
[•] Danger code (Kemler):				
· UN-Number:	3295			
 Packaging group: 	III			
· Hazard label:	3			
 Description of goods: 				
· Limited quantities (LQ)	LQ7			
· Remarks:	Is not subject to the ADR/RID according to 2.2.3.1.5 (\leq 450 ltr)			
· Maritime transport IMDG:				
(
· IMDG Class:	3			
· UN Number:	3295			
· Label	3			
 Packaging group: 	III			
· EMS Number:	F-E,S-D			
· Proper shipping name:	HYDROCARBONS, LIQUID, N.O.S., mixture			
· Remarks:	Meets provision 2.3.2.5 of IMDG.			
	In containers <30 ltr no subject to IMDG-chapters 4.1, 5.2 and 6.1			
		(Contd. on page 5)		
		an a		



Printing date 07.12.2009

Revision: 07.12.2009

Trade name: GEBOSIL S-BITUM

(Contd. of page 4)



3

3

•	ICAO/IATA	Class:
	ICAUIAIA	Ulass.

• **UN/ID Number:** 3295

· Label

*

• Packaging group: III

· Proper shipping name: HYDROCARBONS, LIQUID, N.O.S., mixture

15 Regulatory information

• Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Risk phrases:

10 Flammable.

· Safety phrases:

2 Keep out of the reach of children.

16 Keep away from sources of ignition - No smoking.

46 If swallowed, seek medical advice immediately and show this container or label.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

10 Flammable.

- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Product safety department.
- · Contact: Mr. C.J.A. Timmermans
- * Data compared to the previous version altered.